

Technical Data Sheet

Polyester Colour Pastes

Description

High quality blends of organic and/or inorganic pigments which are dispersed in a non-volatile, crosslinking polyester resin incorporating non-harmful fillers and dispersing aids where necessary.

Product Use

For blending and tinting into unsaturated polyester gelcoats and resins.

Colour Fastness to Light (BS 1006:1990: B02)

*Pigments and types of gelcoats are a factor

Inorganic Dispersions - 7

Organic/Inorganic Dispersions - 7

Organic Dispersions - 7

Acid & Alkali Resistance (measured on a scale of 1 -5)

*Pigments and types of gelcoats are a factor

Inorganic Dispersions - 5

Organic/Inorganic Dispersions - 4-5 (mainly for Alkali)

Organic Dispersions - 4-5

Application

Gently agitate pigment paste before use. Excessive pigment paste dosing in resins or gelcoats will adversely affect product performance.

Storage & Packaging

Store away from any direct sunlight in the original, factory sealed airtight containers. Store below 25°C but freezing conditions must be avoided. The shelf life & properties of pigment pastes can be adversely affected by incorrect storage conditions. Only open containers immediately before use & close airtight after use. Use within 12 months of date of manufacture.



All of our products are manufactured to the highest standards, working to our ISO 9001:2015 system. Only the finest materials and latest technologies are used to ensure product suitability, stability and usability.

We have a choice of standard and next day services on both hazardous and non-hazardous freight.

We offer more than just a technical data sheet. We advise and explain any technical aspect to ensure peace of mind when ordering from Colorplas.