



## Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 1

Gelcoat tub part A

sds no. : 211392  
V003.0

Revision: 23.10.2013  
printing date: 02.01.2014

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Gelcoat tub part A

#### Contains:

Styrene  
Methyl methacrylate

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:  
2K Filler paste

#### 1.3. Details of the supplier of the safety data sheet

Henkel Limited  
Apollo Court, 2 Bishop Square Business Park  
AL10 9EY Hatfield

Great Britain

Phone: +44 (1707) 635000  
Fax-no.: +44 (1707) 635099

ua-productsafety.uk@uk.henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Flammable liquids	Category 3
H226 Flammable liquid and vapor.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: Respiratory tract irritation	
Specific target organ toxicity - repeated exposure	Category 1
H372 Causes damage to organs through prolonged or repeated exposure.	

**Classification (DPD):**

Flammable  
R10 Flammable.  
Xn - Harmful  
R20 Harmful by inhalation.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
Sensitizing  
R43 May cause sensitisation by skin contact.  
Xi - Irritant  
R36/37/38 Irritating to eyes, respiratory system and skin.

**2.2. Label elements**

**Label elements (CLP):**

**Hazard pictogram:**



**Signal word:**

Danger

**Hazard statement:**

H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H372 Causes damage to organs through prolonged or repeated exposure.

**Precautionary statement:**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P501 Dispose of contents/container in accordance with national regulation.

**Precautionary statement:  
Prevention**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P261 Avoid breathing mist/vapours.  
P280 Wear protective gloves.

**Precautionary statement:  
Response**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.

**Label elements (DPD):**

|| Xn - Harmful



**Risk phrases:**

|| R10 Flammable.  
|| R20 Harmful by inhalation.  
|| R36/37/38 Irritating to eyes, respiratory system and skin.  
|| R43 May cause sensitisation by skin contact.  
|| R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**Safety phrases:**

|| S2 Keep out of the reach of children.  
|| S16 Keep away from sources of ignition - No smoking.  
|| S23 Do not breathe vapour.  
|| S24 Avoid contact with skin.  
|| S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
|| S28 After contact with skin, wash immediately with plenty of water and soap.  
|| S37 Wear suitable gloves.

**Contains:**

Styrene,  
Methyl methacrylate

**2.3. Other hazards**

None if used properly.

**SECTION 3: Composition/information on ingredients**

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Styrene 100-42-5	202-851-5 01-2119457861-32	20- 30 %	Flammable liquids 3 H226 Acute toxicity 4; Inhalation H332 Aspiration hazard 1 H304 Serious eye irritation 2 H319 Skin irritation 2 H315 Specific target organ toxicity - single exposure 3 H335 Specific target organ toxicity - repeated exposure 1; Inhalation H372
Methyl methacrylate 80-62-6	201-297-1 01-2119452498-28	1- 5 %	Flammable liquids 2 H225 Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315 Skin sensitizer 1 H317
Methanol 67-56-1	200-659-6 01-2119433307-44	0,1- 1 %	Flammable liquids 2 H225 Acute toxicity 3; Inhalation H331 Acute toxicity 3; Dermal H311 Acute toxicity 3; Oral H301 Specific target organ toxicity - single exposure 1 H370

For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.

**Declaration of ingredients according to DPD (EC) No 1999/45:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Styrene 100-42-5	202-851-5 01-2119457861-32	20 - 30 %	R10 Xn - Harmful; R20, R48/20, R65 Xi - Irritant; R36/37/38
Methyl methacrylate 80-62-6	201-297-1 01-2119452498-28	1 - 5 %	Xi - Irritant; R37/38 R43 F - Highly flammable; R11
Methanol 67-56-1	200-659-6 01-2119433307-44	0,1 - 1 %	T - Toxic; R23/24/25, R39/23/24/25 F - Highly flammable; R11

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.  
Substances without classification may have community workplace exposure limits available.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**

IF ON SKIN: Wash with plenty of soap and water.  
Seek medical advice.

**Eye contact:**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical advice.

**Ingestion:**

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.  
Seek medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

SKIN: Redness, inflammation.

Causes serious eye irritation.

May cause an allergic skin reaction.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

## SECTION 5: Firefighting measures

**5.1. Extinguishing media**

**Suitable extinguishing media:**

Carbon dioxide, foam, powder

**5.2. Special hazards arising from the substance or mixture**

In case of fire, keep containers cool with water spray.  
Oxides of carbon, oxides of nitrogen, irritating organic vapors.

**5.3. Advice for firefighters**

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

**Additional information:**

Do not inhale vapors and fumes.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Remove sources of ignition.  
Ensure adequate ventilation.

**6.2. Environmental precautions**

Do not let product enter drains.

**6.3. Methods and material for containment and cleaning up**

For large spills absorb onto inert absorbent material and place in sealed container for disposal.  
For small spills wipe up with paper towel and place in container for disposal.  
Wash spillage site thoroughly with soap and water or detergent solution.

**6.4. Reference to other sections**

See advice in chapter 8

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**

Do not inhale vapors and fumes.  
Avoid skin and eye contact.  
Keep away from sources of ignition - no smoking.  
Use only in well-ventilated areas.

## Hygiene measures:

- Wash hands before work breaks and after finishing work.
- Do not eat, drink or smoke while working.
- Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

- Keep away from sources of ignition.
- Store in a cool, well-ventilated place.

**7.3. Specific end use(s)**

- 2K Filler paste

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**

- Valid for
- Great Britain

Ingredient	ppm	mg/m <sup>3</sup>	Type	Category	Remarks
STYRENE 100-42-5	250	1.080	Short Term Exposure Limit (STEL):		EH40 WEL
STYRENE 100-42-5	100	430	Time Weighted Average (TWA):		EH40 WEL
TITANIUM DIOXIDE, RESPIRABLE 1317-70-0		4	Time Weighted Average (TWA):		EH40 WEL
TITANIUM DIOXIDE, TOTAL INHALABLE 1317-70-0		10	Time Weighted Average (TWA):		EH40 WEL
SILICA, AMORPHOUS, INHALABLE DUST 112945-52-5		6	Time Weighted Average (TWA):		EH40 WEL
SILICA, AMORPHOUS, RESPIRABLE DUST 112945-52-5		2,4	Time Weighted Average (TWA):		EH40 WEL
METHYL METHACRYLATE 80-62-6	100	416	Short Term Exposure Limit (STEL):		EH40 WEL
METHYL METHACRYLATE 80-62-6	50	208	Time Weighted Average (TWA):		EH40 WEL
METHANOL 67-56-1	200	266	Time Weighted Average (TWA):		EH40 WEL
METHANOL 67-56-1			Skin designation:	Can be absorbed through the skin.	EH40 WEL
METHANOL 67-56-1	250	333	Short Term Exposure Limit (STEL):		EH40 WEL
METHANOL 67-56-1	200	260	Time Weighted Average (TWA):	Indicative	ECLTV

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Styrene 100-42-5	aqua (freshwater)					0,028 mg/L	
Styrene 100-42-5	aqua (marine water)					0,0028 mg/L	
Styrene 100-42-5	aqua (intermittent releases)					0,04 mg/L	
Styrene 100-42-5	STP					5 mg/L	
Styrene 100-42-5	sediment (freshwater)					0,614 mg/kg	
Styrene 100-42-5	sediment (marine water)					0,0614 mg/kg	
Styrene 100-42-5	soil					0,2 mg/kg	
Methyl methacrylate 80-62-6	aqua (freshwater)					0,94 mg/L	
Methyl methacrylate 80-62-6	aqua (marine water)					0,094 mg/L	
Methyl methacrylate 80-62-6	aqua (intermittent releases)					0,94 mg/L	
Methyl methacrylate 80-62-6	STP					10 mg/L	
Methyl methacrylate 80-62-6	sediment (freshwater)					5,74 mg/kg	
Methyl methacrylate 80-62-6	soil					1,47 mg/kg	
Methanol 67-56-1	aqua (freshwater)					154 mg/L	
Methanol 67-56-1	sediment (freshwater)					570,4 mg/kg	
Methanol 67-56-1	aqua (marine water)					15,4 mg/L	
Methanol 67-56-1	soil					23,5 mg/kg	
Methanol 67-56-1	STP					100 mg/L	

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Styrene 100-42-5	worker	inhalation	Acute/short term exposure - systemic effects		289 mg/m3	
Styrene 100-42-5	worker	inhalation	Acute/short term exposure - local effects		306 mg/m3	
Styrene 100-42-5	worker	Dermal	Long term exposure - systemic effects		406 mg/kg	
Styrene 100-42-5	worker	inhalation	Long term exposure - systemic effects		85 mg/m3	
Styrene 100-42-5	general population	inhalation	Acute/short term exposure - systemic effects		174,25 mg/m3	
Styrene 100-42-5	general population	inhalation	Acute/short term exposure - local effects		182,75 mg/m3	
Styrene 100-42-5	general population	Dermal	Long term exposure - systemic effects		343 mg/kg	
Styrene 100-42-5	general population	inhalation	Long term exposure - systemic effects		10,2 mg/m3	
Styrene 100-42-5	general population	oral	Long term exposure - systemic effects		2,1 mg/kg	
Methyl methacrylate 80-62-6	worker	Dermal	Acute/short term exposure - local effects		1,5 mg/cm2	
Methyl methacrylate 80-62-6	worker	Dermal	Long term exposure - systemic effects		13,67 mg/kg bw/day	
Methyl methacrylate 80-62-6	worker	inhalation	Long term exposure - systemic effects		210 mg/m3	
Methyl methacrylate 80-62-6	worker	Dermal	Long term exposure - local effects		1,5 mg/cm2	
Methyl methacrylate 80-62-6	worker	inhalation	Long term exposure - local effects		210 mg/m3	
Methyl methacrylate 80-62-6	general population	Dermal	Acute/short term exposure - local effects		1,5 mg/cm2	
Methyl methacrylate 80-62-6	general population	Dermal	Long term exposure - systemic effects		8,2 mg/kg bw/day	
Methyl methacrylate 80-62-6	general population	inhalation	Long term exposure - systemic effects		74,3 mg/m3	
Methyl methacrylate 80-62-6	general population	Dermal	Long term exposure - local effects		1,5 mg/cm2	
Methyl methacrylate 80-62-6	general population	inhalation	Long term exposure - local effects		105 mg/m3	
Methanol 67-56-1	worker	Dermal	Acute/short term exposure - systemic effects		40 mg/kg bw/day	
Methanol 67-56-1	worker	inhalation	Acute/short term exposure - systemic effects		260 mg/m3	
Methanol 67-56-1	worker	inhalation	Acute/short term exposure - local effects		260 mg/m3	
Methanol 67-56-1	worker	Dermal	Long term exposure - systemic effects		40 mg/kg bw/day	
Methanol 67-56-1	worker	inhalation	Long term exposure -		260 mg/m3	



			systemic effects		
Methanol 67-56-1	worker	inhalation	Long term exposure - local effects		260 mg/m <sup>3</sup>
Methanol 67-56-1	general population	Dermal	Acute/short term exposure - systemic effects		8 mg/kg bw/day
Methanol 67-56-1	general population	inhalation	Acute/short term exposure - systemic effects		50 mg/m <sup>3</sup>
Methanol 67-56-1	general population	oral	Acute/short term exposure - systemic effects		8 mg/kg bw/day
Methanol 67-56-1	general population	inhalation	Acute/short term exposure - local effects		50 mg/m <sup>3</sup>
Methanol 67-56-1	general population	Dermal	Long term exposure - systemic effects		8 mg/kg bw/day
Methanol 67-56-1	general population	inhalation	Long term exposure - systemic effects		50 mg/m <sup>3</sup>
Methanol 67-56-1	general population	oral	Long term exposure - systemic effects		8 mg/kg bw/day
Methanol 67-56-1	general population	inhalation	Long term exposure - local effects		50 mg/m <sup>3</sup>

**Biological Exposure Indices:**

None

**8.2. Exposure controls:****Respiratory protection:**

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Avoid eye contact.

Wear protective glasses.

**Skin protection:**

Wear protective equipment.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance

paste  
white

Odor

characteristic

Odour threshold

No data available / Not applicable

pH	No data available / Not applicable
Initial boiling point	> 100,0 °C (> 212 °F)
Flash point	32,0 °C (89.6 °F); Supplier method
Decomposition temperature	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Density	1,34 g/cm <sup>3</sup>
( )	
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Insoluble
(Solvent: Water)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

## 9.2. Other information

No data available / Not applicable

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None if used properly.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.

### 10.5. Incompatible materials

See section reactivity

### 10.6. Hazardous decomposition products

carbon oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### Oral toxicity:

May cause irritation to the digestive tract.

#### Inhalative toxicity:

May cause respiratory irritation.

**Skin irritation:**

Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.  
Causes skin irritation.

**Eye irritation:**

Causes serious eye irritation.

**Sensitizing:**

May cause an allergic skin reaction.

**Acute oral toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Styrene 100-42-5	LD50	6.600 - 8.000 mg/kg	oral		rat	
Styrene 100-42-5	Acute toxicity estimate (ATE)	6.600 mg/kg				Expert judgement
Methanol 67-56-1	LD50	7.914 mg/kg	oral		rat	
Methanol 67-56-1	Acute toxicity estimate (ATE)	100 mg/kg				Expert judgement

**Acute inhalative toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Styrene 100-42-5	LC50	11,8 mg/l	inhalation	4 h	rat	
Methanol 67-56-1	LC50	87,5 mg/l	inhalation	6 h	rat	
Methanol 67-56-1	Acute toxicity estimate (ATE)	3 mg/l				Expert judgement

**Acute dermal toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Styrene 100-42-5	LD50	> 2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methanol 67-56-1	not irritating		rabbit	

**Serious eye damage/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methanol 67-56-1	not irritating		rabbit	

**Respiratory or skin sensitization:**

Hazardous components CAS-No.	Result	Test type	Species	Method
Styrene 100-42-5	not sensitising	Guinea pig maximisation test	guinea pig	
Methyl methacrylate 80-62-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Methanol 67-56-1	not sensitising	Guinea pig maximisation test	guinea pig	

**Germ cell mutagenicity:**

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Styrene 100-42-5	positive	sister chromatid exchange assay in mammalian cells	with and without		OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Styrene 100-42-5	negative	inhalation: vapour		mouse	
Methyl methacrylate 80-62-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		

**Carcinogenicity:**

Hazardous components CAS-No.	Result	Species	Sex	Exposure timeFrequency of treatment	Route of application	Method
Styrene 100-42-5	not carcinogenic	rat	male/female	104 weeks; 9 or 10 rats per... 6 hours/day, 5 days/week	inhalation: vapour	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Repeated dose toxicity**

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Styrene 100-42-5	NOAEL=1.000 mg/kg	oral: gavage	daily (5 days/week)	rat	
Styrene 100-42-5	NOAEL=> 60 mg/kg	intraperitoneal	14 days	rat	
Methyl methacrylate 80-62-6	NOAEL=1000 ppm	inhalation	14 weeks 6 hrs/day, 5 days/wk	mouse	
Methanol 67-56-1	NOAEL=6,63 mg/l	inhalation	4 weeks 6 h/d, 5 d/w	rat	

**SECTION 12: Ecological information****General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

**12.1. Toxicity****Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Styrene 100-42-5	LC50	10 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Styrene 100-42-5	EC50	4,7 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Styrene 100-42-5	EC50	6,3 mg/l	Algae	96 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
	EC10	0,28 mg/l	Algae	96 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Styrene 100-42-5	NOEC	1,01 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Methyl methacrylate 80-62-6	LC50	350 mg/l	Fish		Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methyl methacrylate 80-62-6	EC50	69 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methyl methacrylate 80-62-6	EC50	170 mg/l	Algae	4 d	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	100 mg/l	Algae	4 d	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methanol 67-56-1	NOEC	7.900 mg/l	Fish	200 h	Oryzias latipes	
Methanol 67-56-1	LC50	> 1.000 mg/l	Fish	48 h	Leuciscus idus	
Methanol 67-56-1	EC50	> 10.000 mg/l	Daphnia	48 h	Daphnia magna	
Methanol 67-56-1	EC50	28,44 g/l	Algae		Chlorella pyrenoidosa	OECD Guideline 201 (Alga, Growth Inhibition Test)

## 12.2. Persistence and degradability

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Styrene 100-42-5	readily biodegradable	aerobic	87 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Methyl methacrylate 80-62-6	readily biodegradable	aerobic	95 %	EU Method C.4-B (Determination of the "Ready" Biodegradability Modified OECD Screening Test)
Methanol 67-56-1	readily biodegradable	aerobic	82 - 92 %	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)

## 12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Styrene 100-42-5		74				
Styrene 100-42-5	2,96				25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Methyl methacrylate 80-62-6	1,38					
Methanol 67-56-1	-0,77					

**12.5. Results of PBT and vPvB assessment**

<b>Hazardous components CAS-No.</b>	<b>PBT/vPvB</b>
Methyl methacrylate 80-62-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Methanol 67-56-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**12.6. Other adverse effects**

No data available.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Product disposal:

Incineration under controlled conditions is recommended.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

**SECTION 14: Transport information****14.1. UN number**

ADR	2055
RID	2055
ADNR	2055
IMDG	2055
IATA	2055

**14.2. UN proper shipping name**

ADR	STYRENE MONOMER, STABILIZED (solution)
RID	STYRENE MONOMER, STABILIZED
ADNR	STYRENE MONOMER, STABILIZED
IMDG	STYRENE MONOMER, STABILIZED (EH&S)
IATA	Styrene monomer, stabilized (34726010)

**14.3. Transport hazard class(es)**

ADR	3
	3
RID	3
	3
ADNR	3
	3
IMDG	3
	3
IATA	3
	3

**14.4. Packaging group**

ADR	III
RID	III
ADNR	III
IMDG	III
IATA	III

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADNR	not applicable
IMDG	not applicable
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable
	Tunnelcode: (D/E)
RID	not applicable
ADNR	not applicable
IMDG	not applicable
IATA	not applicable

When transporting as a set (component A and B) then the following dangerous good classification is used: UN 3269 Polyester resin kit, 3, III.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 30,00 %  
(1999/13/EC)

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

R10 Flammable.  
R11 Highly flammable.  
R20 Harmful by inhalation.  
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.  
R36/37/38 Irritating to eyes, respiratory system and skin.  
R37/38 Irritating to respiratory system and skin.  
R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.  
R43 May cause sensitisation by skin contact.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R65 Harmful: may cause lung damage if swallowed.  
H225 Highly flammable liquid and vapor.  
H226 Flammable liquid and vapor.  
H301 Toxic if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H370 Causes damage to organs.  
H372 Causes damage to organs through prolonged or repeated exposure.

### Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.